



CARFIL QUALITY
YOUR SUPPLIER FOR ALL LABORATORY NEEDS

Capnotrue® AMP Mainstream CO₂/SPO₂ Monitors (for rats and large animals)



Features

Advanced and reliable capnograph and pulse oximeter combined in a single monitor.

- Mainstream CO₂ measurement with the IRMA™ CO₂ analyzer
- Warm-up time: < 10s full specification
- Direct measurement without time delay
- Small, light-weight and shock-resistant: the IRMA™ CO₂ analyzer weighs less than 30 g
- Adult/paediatric, infant/neonatal, and a **for rat modified** IRMA™ airway adapter
- Plug and measure technology
- IRMA™ airway adapters with non-condensing light transmission XTP™ window
- No occlusion by water or mucus possible
- Full range of key technology accessories
- Maintenance and calibration-free technology
- Wide range of high-quality SpO₂ sensors

Delivery Package

- Mainstream device
- IRMA™ CO₂ analyser
- Reusable SpO₂ sensor
- CapnoTrue® power supply (EU and UK plug)
- USB data cable
- IRMA™ airway adapter (adult/paediatric)
- Instruction manual
- 1 Li-ion rechargeable battery
- PC software
- 4 batteries (AA)

The CapnoTrue AMP Mainstream Monitor can be used in combination with the uno MiCroVenTiLaTor -



PAVAN SERVICE BVBA

Beyntellus 3 - B-2360 Oud-Turnhout - Tel. +32 (0)14 45 13 10 - admin@carfil.be - BTW BE 0420.681.872

www.carfil.be



CARFIL QUALITY
YOUR SUPPLIER FOR ALL LABORATORY NEEDS

uMV-03.

The CapnoTrue AMP and ASP - CO₂/SpO₂ monitors including the IRMA™ CO₂ analyzer, ISA™ CO₂ analyzer and SoftCap Sensors are classified and certified as class IIb products.

Technical specifications

Measurement range	EtCO ² and FICO ²	0-15%
	SpO ²	0-100%
	Respiration rate	0-150 breaths/min
	Pulse rate	20-300 beats/min
Accuracy	EtCO ² and FICO ²	+/- (0.2 vol % + 2% of reading) +/- (0.3 vol % + 4% of reading) incl. interfering gas
	SpO ²	+/- 2% (70-100%)
	Respiration rate	+/-1 digit at 60 breaths/min
	Pulse rate	+/- ditit (uop to 100/min) or +/- 1% (<100/min)
Display		
Characteristics	Active OLED colour graphic display, 262.000 colours, 240 x 320 dots	
Displayed data	End-tidal CO ² and inspired CO ² in vol %, kPa or mmHg, oxygen saturation, respirationrate, pulse rate, capnogram, plethysmogram and short term trend	
Indicators	Signal strength and signal quality, pulse amplitude, battery status, alarm mut, pulse tone mute, neonatal mode, time	
Trend information		
Long term trend	up to 400 hours	
Short term trend	15 min/1h/6h	
Language versions		
	Englisch	(additional language versions on request)
Environmental conditions		
Operation	0 - 50°C, 15 - 95% r.H. (non-condensing), 60 - 120 kPa (excl. Li-ion battery)	
Storage	-30 - 70°C, 10 - 95% r.H. (non- condensing),60 - 120 kPa (excl. Li-ion battery)	
Classification		
Product class	IIb (in accordance with MDD 93 / 42 / EEC)	
Safety	Class of protection II / type BF	



PAVAN SERVICE BVBA

Beyntellus 3 - B-2360 Oud-Turnhout - Tel. +32 (0)14 45 13 10 - admin@carfil.be - BTW BE 0420.681.872

www.carfil.be



CARFIL QUALITY

YOUR SUPPLIER FOR ALL LABORATORY NEEDS

Construction	IPX1
Standards	EN 60601-1:2006, EN 60601-1-1:2001, EN 60601-1-2:2007, EN 60601-1-8:2004, DIN EN 60529, EN ISO 21647:2004, EN ISO 9919:2005
Miscellaneous	
Dimensions	(LxWxD) 150 mm x 75 mm x 35 mm
Weight	<400 g (complete device with batteries)
Power supply	90-260 VAC/6 VDC, 50-60 Hz, 4 AA batteries, 2.5 Ah Li-ion battery
Battery capacity	up to 6 hours continuous operation
Communication interface	USB 2.0

Ordering number

180000170	Capnotrue AMP
180000172	Adjusted Probe to be used with Rats
180000173	Probe to be used with larger Animals



PAVAN SERVICE BVBA

Beyntellus 3 - B-2360 Oud-Turnhout - Tel. +32 (0)14 45 13 10 - admin@carfil.be - BTW BE 0420.681.872

www.carfil.be