



CARFIL QUALITY
YOUR SUPPLIER FOR ALL LABORATORY NEEDS

Data Loggers DST Centi



Features

DST Centi - miniature submersible temperature data logger

- Self-contained temperature logger ideal for use in environmental temperature monitoring
- High pressure survival up to 3000 m depth
- Biocompatible housing suitable for implantation in animals
- Long battery life of 9 years
- Small sized logger with dimensions 46 mm x 15 mm
- Large memory of 174,000 measurements (can be extended)

The DST centi-T is a miniature submersible temperature data logger. Recorded data is stored in its internal memory with a real-time clock reference for each measurement.

The self-contained temperature logger is supported by the SeaStar software and the Communication Box which serves as an interface between the logger and a PC. Communication between the logger and the Communication Box is wireless.

In SeaStar, the user sets the start time, start date and sampling interval before starting the recorder. Up to seven different intervals can be set for the same measurement sequence. This is especially useful when more frequent measurements are needed at a certain time period.

After recovering the DST recorded data is uploaded via to SeaStar where results are displayed both in graphic and tabular form. After retrieving the data, the DST can be re-programmed and reused as long as the battery lasts. A set of Communication Box and SeaStar software needs to be purchased with the first order.

The DST centi-T temperature logger is suitable for studies within e.g.:

- Temperature fluctuations in animals
- Thermistor chain in water columns
- Temperature monitoring in oceans, rivers and lakes
- Agricultural research projectsAquaculture studies
- Aquaculture studies



PAVAN SERVICE BVBA

Beyntellus 3 - B-2360 Oud-Turnhout - Tel. +32 (0)14 45 13 10 - admin@carfil.be - BTW BE 0420.681.872

www.carfil.be



CARFIL QUALITY
YOUR SUPPLIER FOR ALL LABORATORY NEEDS

Technical specifications

Sensors	Temperature
Size	46 mm x Ø 15 mm
Housing Material	Alumina (Ceramic)
Weight in air/in water	In Air: 19 gram / In water: 12 gram
Memory type	Non-volatile EEPROM
Memory capacity	174,000 measurements
Memory capacity bytes	261,819 Bytes / temp 1,5 byte
Memory management	Custom programming
Data resolution	12 bits
Temperature resolution	0,032°C
Temperature accuracy	+/- 0,1°C
Temperature range	5 to 45°C
Temperature response time	Time constant (63%) reached in 20sec
Data retention	25 years
Clock	Real time clock, accuracy +/- 1 min/month
Sampling Interval	User specified in seconds, minutes or hours
Number of different sampling intervals	1 to 7
Communications	Communication box, RS232C 9 pin serial or USB
Battery life	108 months - with a sampling interval of 10 min at room temp. Non-replaceable batteries



PAVAN SERVICE BVBA

Beyntellus 3 - B-2360 Oud-Turnhout - Tel. +32 (0)14 45 13 10 - admin@carfil.be - BTW BE 0420.681.872

www.carfil.be