



CARFIL QUALITY
YOUR SUPPLIER FOR ALL LABORATORY NEEDS

UNO Universal Static Reader



Features

This stationary reader has a good reading distance with reader activation placed under software control or trigger controlled.

Transponders that can be read

- UNO PICO ID Transponders
- UNO MICRO ID/8Transponders
- UNO MICRO ID/12Transponders
- Trovan® Unique & Flex
- ISO FDX-B
- Destron (Fecava)
- AVID
- ASK
- PSK1 and PSK2Transponders
- AVID Encrypted tags.

Standard version

- Probe antenna (ANT613S)
- Reads automatically when transponder is near antenna
- Needs regulated 12VDC $\pm 5\%$ linear powersupply
- Relay output, selectable potential free or 12VDCno/nc.
- Buzzer onboard
- 512kb EEprom for datastorage
- Windows NT/XP/Vista/7 PCsoftware
- USB output for communication withWinwedge
- Dimensions: 25,5 x 18 x 8,5cm
- Weight: 1Kg



PAVAN SERVICE BVBA

Beyntellus 3 - B-2360 Oud-Turnhout - Tel. +32 (0)14 45 13 10 - admin@carfil.be - BTW BE 0420.681.872

www.carfil.be



CARFIL QUALITY
YOUR SUPPLIER FOR ALL LABORATORY NEEDS

Available Antennas

1. **External single coil probe antenna (ANT613S)**
2. **External Single Coil Antenna (ANT 616): To be positioned at the wall inside a laminar flow cabinet and the reader can be kept outside of the cabinet.**



PAVAN SERVICE BVBA

Beyntellus 3 - B-2360 Oud-Turnhout - Tel. +32 (0)14 45 13 10 - admin@carfil.be - BTW BE 0420.681.872

www.carfil.be